


## SX600 Series

Brass head container and stainless steel vessel for industrial use with high standards of mechanical resistance and reliability in high temperature applications

### Technical features

- Max operating pressure 15 bar
- Min/max operating temperature 0°C/90°C
- Head and ring in nickel-plated brass
- Provision for pressure gauges
- Pressure relief screw
- Mountable in the ½" – ¾" – 1" versions
- Heads with 1"1/4 - 1"½ - 2" connections mount GTS or XSM cartridges



### AISI 304 vessel - without drain

Item code	Description	attacks	H cartridge	l (mm)	H (mm)	Flow rate (l/h)	Pieces for conf.
0a6050380	SX600	½"	5"	135	185	6000	12
0a6050480	SX600	¾"	5"	135	185	6000	12
0a6050580	SX600	1"	5"	135	185	6000	12
0a6070380	SX600	½"	7"	135	235	6000	6
0a6070480	SX600	¾"	7"	135	235	6000	6
0a6070580	SX600	1"	7"	135	235	6000	6
0a6090380	SX600	½"	9" ¾	135	337	6000	6
0a6090480	SX600	¾"	9" ¾	135	337	6000	6
0a6090580	SX600	1"	9" ¾	135	337	6300	6
0a6100680	SX600	1" ¼	9" ¾	150	355	12000	6
0a6100780	SX600	1" ½	9" ¾	150	355	13000	6
0a6100880	SX600	2"	9" ¾	162	363	14000	6
0a6200480	SX600	¾"	20"	135	565	6000	6
0a6200580	SX600	1"	20"	135	565	6300	6
0a6200680	SX600	1" ¼	20"	150	587	12000	6
0a6200780	SX600	1" ½	20"	150	587	13000	6
0a6200880	SX600	2"	20"	162	595	14000	6



### AISI 304 vessel - with ½" threaded drain

Item code	Description	attacks	H cartridge	l (mm)	H (mm)	Flow rate (l/h)	Pieces for conf.
0a6050381	SX600sc	½"	5"	135	185	6000	12
0a6050481	SX600sc	¾"	5"	135	185	6000	12
0a6050581	SX600sc	1"	5"	135	185	6000	12
0a6070381	SX600sc	½"	7"	135	235	6000	6
0a6070481	SX600sc	¾"	7"	135	235	6000	6
0a6070581	SX600sc	1"	7"	135	235	6000	6
0a6090381	SX600sc	½"	9" ¾	135	337	6000	6
0a6090481	SX600sc	¾"	9" ¾	135	337	6000	6
0a6090581	SX600sc	1"	9" ¾	135	337	6300	6
0a6100681	SX600sc	1" ¼	9" ¾	150	355	12000	6
0a6100781	SX600sc	1" ½	9" ¾	150	355	13000	6
0a6100881	SX600sc	2"	9" ¾	162	363	14000	6
0a6200481	SX600sc	¾"	20"	135	565	6000	6
0a6200581	SX600sc	1"	20"	135	565	6300	6
0a6200681	SX600sc	1" ¼	20"	150	587	12000	6
0a6200781	SX600sc	1" ½	20"	150	587	13000	6
0a6200881	SX600sc	2"	20"	162	595	14000	6

